

New columns for architecture in reinforced concrete

David Jolly Monge

INTRODUCTION

Reinforced concrete is a key building material of modern architecture and the habitable infrastructure of today's world. This is due to the extraordinary virtues met in this material: mechanical resistance with incombustibility and resistance to high temperatures.

This artificial material, taking this adjective in its direct sense, uniting the terms art and craft, is basically made up of two components: a steel structure which is covered by cement in a semi-liquid state which after a physical-chemical process passes from an amorphous moldable state to a solid which acquires the resistance to compression that characterizes it, the steel inside responsible for resisting tension, forming an element that resists both forces in a calculable and predictable way

Now the virtues of this material are limited by its condition of moldability, that must be maintained for the duration of curing by a container which gives it a form.

And the form is the issue to which architects devote themselves: the form of the limits which construct the spaces we inhabit. That is why this research into the form that reinforced concrete can acquire has been addressed by architects. Now we can confirm that the greatest number of forms given to elements or parts built with concrete have something in common: they are formed by rectilinear planes. The volumetric elements constructed with concrete thus have a prismatic form, said generally to be through the intersection of rectilinear planes (West, 2016); with them, you cannot access to double curve continuous mantles, only an approximation with a prism on many faces but that solution is expensive.

Exceptions exist, amongst whom we note Miguel Fisac (1913-2006) who used flexible formwork to give a plastic surface to the exterior of his works in concrete. In the early twentieth century, some patents involving its use appear, and the real development of this technology in this century, begins with a laboratory dedicated to this purpose CAST (Centre for Architectural Structures and Technology), founded by architect Mark West in Canada in 2002 (Veenendaal, West, & Block, 2011). And a number of researchers that started demonstrating the advantages of this technology, among them its improvement to the hardness of concrete on its surface because it expels the excess water from the mortar, as verified in a research in the University of Bath (Orr, 2012). Also some non prismatic columns may carry twice the load at equal amounts of concrete depending on their form. (Pedreschi, 2015). Flexible formworks are among a 100 to 300 lighter than a traditional formwork, and could be used several times, and may cost ten times less (West, 2005). And that 'fabric form-work is structurally safe alternative for forming reinforced concrete columns' (Delijani, West, & Svecova, 2015)

-Reinforced
concrete
-virtues

El hormigo sirve como material de construcción y de uso múltiple. Posee extraordinarias virtudes de resistencia e incombustibilidad.

-components
-resistance
-cement

El proceso estructura se basa en la enfierradura interior, y el semi líquido que lo envuelve y se modifica

-virtues
-moldability

El material al ser moldeable requiere ser contenido en un recipiente.

-form
-spaces
-rectilinear

Se construye el espacio con los límites. Los moldajes de hormigón crean formas rectilíneas y no hacen posible uno curvo.

-formwork
-plastic surface
-advantages
-alternative
-structurally safe

Con el trabajo de Miguel Fisac, y posteriormente con el laboratorio CAST, se investiga acerca de las posibilidades del hormigón en encofrados flexibles, entre ellas destacan sus ventajas prácticas en relación al costo de realización y su practicidad y reutilización en relación con el método tradicional de trabajar este material.

The research presented here thanks to Fondecyt (FONDECYT, Fondo Nacional de Desarrollo Científico y Tecnológico), Project N° 11140640 developed in Corporación Cultural Amereida, Quintero, Chile, "Concrete Architectonic form done with flexible formworks", takes another step towards opening up a new field of organic forms for architecture made with reinforced concrete elements. It seeks to open two possibilities simultaneously: firstly proportioning new forms of architecture and secondly, realizing these forms at the location where the building is taking place, i.e. in situ. This is because until now research in this field has realized such construction elements either in the laboratory or the factory space of the prefabrication industry. Now we have taken this research to the building site, extending the possibility of this kind of manufacture to all places where works of architecture are being built.

-organic
-new forms
-prefabrication
.posibility
-place

Las experimentaciones que hicieron aportaron con el desarrollo a nuevas formas orgánicas, ampliando posibilidad de su fabricación.

The methodology consists of an experiment task done in a construction workshop. This is divided into two basic steps, first building scale models done on the workshop. The second step is the prototype testing which is done in full scale 1:1 in a work of architecture (Models are done in plaster scaled 1:10. Prototypes are done on reinforced concrete scale 1:1)

-experiment
-scale models
-prototype

La metodología consiste en experimentar en talleres con modelos a escalas y luego probarlos a una escala real.

The methodology of work with architectural models operates with a procedure which can distinguish at least three steps, the first is to imagine a possible form, whether is a mental proposition or may be recognized in an existing body, then this figure is translated to a drawing or other mode of representation, allowing a formal purpose, who leads to the next step that is some realization. This research sought to achieve new forms of architecture in concrete with flexible formwork. The design strategy was to find new forms for a primary architectural element: the vertical column.

-Experiment task
-building
-full scale

El desarrollo se realiza en tres pasos, pensar en una forma posible, representarla mediante un dibujo, y realizarla

This whole argument is rooted in a simple but radical fact: the formwork for reinforced concrete has changed from being made exclusively of rigid materials to incorporating flexible material such as fabrics and membranes. The cement of the concrete is contained by a thin sheet of fabric where a negotiation is produced between the semi-liquid mass and the fabric that resists tension, fabric, and cement arriving at an equilibrium shape through gravity, which makes its volume fill a peculiar form. This peculiarity that belongs to a state of wet weight makes us name it an 'organic form', as once rigid, its form with double curvatures sometimes recalls the organic nature of living bodies.

-flexible
-volume
-equilibrium
-organic form

Se sustituyen los elementos rígidos del molde por membranas exibles, logrando formas mas orgánicas.

There is also another research way opening by this days, as the forms obtained with flexible formworks are not possible to predict with digital models, research knowledge may be improved by the techniques of massive data capture (Lluis i Ginovart, Costa-Jover, Coll-Plà, & Puche-Fontanilles, 2016). Measuring the differences on what is projected and what is obtained in the models and prototypes. This accurate technology may also help the structural analysis of this new forms.

-new forms
-data capture
-differences

La predicción con modelos digitales puede servir para una recopilación de datos.

Eight shapes for a column obtained out of the basic figure of a cylinder. The difference among them is obtained from the number of a rigid matrices: one or two; the number of fabric sheets, and the profile of the rigid matrix.

-column obtained
-rigid matrices

8 columnas obtenidas a base de cilindros matrices lo unico que las diferencias, ya sea en su forma y cantidad.

Methodology

This research is conducted by postulating a methodological thesis, which holds that a scale model has a similar behavior to that of a full-scale 1:1 prototype, in terms of the form (Jolly, Eyquem, & Jolly, 2011). That is to say, the form obtained in a scale model and with a much finer-grained material, gypsum plaster, modeling the concrete, is likely to be able to work at full-scale; and very importantly, what will not work at reduced scale will not work at full scale

-similar behavior
-full scale

Esta investigación da cuenta de la similitud de resultados entre los modelos a escala y los modelos habitables 1:1.

At this point, it is important to discuss the aim concerning location that this research project envisaged from the outset. Early studies and research with flexible formwork for concrete have been done basically in two arenas: workshops or laboratories and the precast-concrete fabrication industry. Both represent a working environment protected from the spatial conditions presented by a building site. For this reason, this project started by proposing that the full-scale 1:1 prototypes would be realized on the site of a project so that what is made is subject to the requirements of a typical building process and in turn could be replicated anywhere a project is erected not just in a laboratory or factory.

-location
-working environment
-laboratories
-replicated

La construcción en obra permite el estudio de un método accesible para cualquier otra obra.

This working thesis confirms the previous findings of Veenendaal & Block (2012), who argue that physical models cannot be replaced by digital models in the use of exible formwork to determine what it is possible to design, and more importantly, that the physical model discloses how you can nally build the element in question. This basic argument opens the possibility of research in the workshop, which is now known as design research (research by design). So the knowledge gained up to date is based on the experience of laboratories and workshops.

-replaced
-build
-experience
-possibility

Los modelos en físico no pueden ser reemplazados por predcciones digitales, dando importancia a la investigación por diseño

Therefore, in accordance with the thesis proposed, the research has experimented with models at 1:10 scale with columns of a section equal to 1/10 of their height, i.e. plaster models of a section of the order of 3 cm in diameter and 30 cm high. Alternatives to the vertical profile of columns with a cylindrical section of equal diameter at the base and the head have been done.

-experimented
-alternatives
-section

Se trabajaron los modelos pero a escalas 1:10 y con perfiles circulares.

Experimentation with flexible formworks has led the development of new forms. And the word new means at least two dimensions, the first is a new figure, their profile, the continuity of double curved surfaces in three-dimensional bodies. The second dimension is that these bodies are obtained through a relative simple constructive operations

-Experimentation
-figure
-simple

La experimentación abre espacio a nuevas figuras.

About 112 models were made, which can basically be classified into two large families that concern their mode of construction: with one vertical rigid matrix and with two such matrices (Figure 1).

-classified
-vertical
-matrices

Se realizaron varios modelos a escala, obteniendo varios prototipos de yeso

<p>The methodology of the workshop process is to give shape to the flexible formwork by fixing the fabric to wooden brackets that permit it to receive the gypsum plaster (Figure 2). The plaster has a slightly different behavior to concrete. Since it behaves as a liquid this involves having a sealed formwork unnecessary with the concrete. To achieve a model several attempts are made to learn the outcome of each experiment, at this stage regularity is sought, leaving out what is achieved by chance. Thus those examples that achieve a regular continuity of surface, without presenting accidents, folds or wrinkles constitute the models. When it comes to building the columns, control of sections was pursued so that later they could be considered suitable for structural calculation. This is a design restriction which in turn unlocks the variants achieved, all columns have a circular section perpendicular to their length; so all are variants that arise from the basic shape of the cylinder which is the basic matrix of the column.</p>	<ul style="list-style-type: none"> -Shape -different -plaster -continuity -control -variants 	<p>Se busca control en las variantes de la construcción, basados en el cilindro e investigando nuevas formas.</p>	<p>RESULTS</p>	<p>The first result obtained is methodological, the thesis posed concerning the relation between model and prototype is a fruitful method of exploration that oscillates between what the architect imagines and what it is possible to build. This is a genuine path that links what the hand and mind can draw like an arabesque and what can be erected taking into account the weight and behavior of the material. Then a spatial-design-led decision is necessary concerning the shape that can contribute most effectively to the architectural form.</p>	<ul style="list-style-type: none"> -relation -oscillates -method -contribute 	<p>Se estudia entre lo que imaginamos y lo que llevamos al dibujo y se puede obtener.</p>
<p>Amongst the models obtained 11 distinct types could be distinguished according to their profile and the number of matrices and cloth sheets required for their fabrication. Of these, the 8 types considered most apt for a column acting as an architectural element was chosen.</p>	<ul style="list-style-type: none"> -models -fabrication 	<p>Se lograron 11 resultados, y se clasificaron en 8 tipos de columnas.</p>	<p>Thus research into the form that reinforced concrete can take opens the possibility of building architectural elements with a traditional shape like a column with entasis, which could only previously be constructed by stone carving; alongside a range of new forms not deemed possible for architecture previously.</p>	<ul style="list-style-type: none"> -possibility -architectural -traditional 	<p>Nuevas opciones para la Arquitectura aparecen.</p>	
<p>Modeling the figures for the columns in a workshop research is a methodological thesis that may obtain the shape of each one and the way it could be built.</p>	<ul style="list-style-type: none"> -Modeling -built 	<p>La investigación en taller permite el estudio de distintas formas.</p>	<p>Because it determined the selection of column shapes deemed worth building as full-scale prototypes in this case, how the approach 'form that is reticent' was matched to column choice is worth outlining briefly. With all the care and dedication its realization involves, a work of architecture is intended to accommodate human habitation, i.e. inside it life needs to be able to be lived to the full. For this to happen the limits constituted by the architecture are 'removed', they are 'not present' all the time, they do not 'weigh' on inhabitants in order that an interior can be given over to events. In seeking an architectural form that 'withdraws', what is sought through the rhyme of word and action is a situation where the accommodation of action is embodied in the spatial virtue of what is built.</p>	<ul style="list-style-type: none"> -column -habitation -limits -accommodation of actions 	<p>La columna elegida para su realización en una obra debe responder a la virtud espacial que se quiere dar.</p>	
<p>In moving from the model to the prototype not only the dimensions but also the material was changed; thus in the model a thin fabric of an ordinary type typical in garment construction was used whereas in the prototype at scale 1:1 a geotextile fabric, type T2100, used typically in the construction of roads and dams, was employed. It is a fabric that behaves as such, with great tensile strength. Whereas 3 mm and 10 mm plywood plates are used in the models, plates of 20 mm plywood and slats of various square sections are used in the final formwork. In this way what is achieved in the model, shapes of a minimal weight that anticipate a similar behavior in the geotextile fabric combined with the cement, must necessarily translate to the gravitational conditions where the reinforced concrete involves a weight of at least 2.5 tons per cubic meter with the consequent pressure on the fabric. This involves the construction of supports for the fabric adequate to sustain the weight of the concrete and ensure its setting in the shape desired.</p>	<ul style="list-style-type: none"> -material -fabric -final formwork -weight -fabric adequate 	<p>En el modelo real se sustituyen los materiales por unos mas correspondiente, también se tiene en cuenta las variantes del hormigón.</p>	<p>Pursuing this intention, the search for form in the models was directed to identify the shape that achieves the most spatiality with the least variation. For example, a variation in arc-height of 1 cm in the curvature of a column of three meters high is not enough to be perceived, and one of 40 cm, being an isolated built figure, does not allow itself to be used as a column; but an arc-height 5cm out of the usual true vertical leaves the column with a new 'will to form'. So of the 8 most suitable families selected the example that best met this condition of retirement was chosen.</p>	<ul style="list-style-type: none"> -search -variation -perceived -retirement 	<p>Se busca el elemento que signifique más en su entorno espacial, para que tenga una intención, logrando ser percibidas en el tamaño y forma.</p>	
<p>The drawing shows the parts needed to build a column 337 cm high. On upper part the rigid elements that sustain the fabric. On the lower part the textile with its drawing and measures (Figure 3).</p>	<ul style="list-style-type: none"> -rigid elements -textile 	<p>Se muestran las partes necesarias para el modelo.</p>	<p>Then, the second result is the realization of a reasonable number of architectural elements, 17 columns made in situ in the work Pórtico de Los Huéspedes de la Ciudad Abierta (Figure 4). They demonstrate that it is possible to construct architectonic elements in reinforced concrete with extremely simple formwork since in each formwork cloth sheets were used requiring no cuts or seams, the shape given only by trapping the fabrics between the rigid matrices. Finally, the construction on site guarantees the possibility of replicating the process described anywhere a work of architecture can be erected with reinforced concrete (Figure 5).</p>	<ul style="list-style-type: none"> -columns -demonstrate -replicating 	<p>Se demostró la posibilidad de construcción de los modelos y el poder replicarlos</p>	
<p>Once the 8 types of columns had been selected from the models obtained, 17 columns were erected, constituting the threshold of the work entitled Pórtico de Los Huéspedes, de la Ciudad Abierta.(de Arce, Oyarzun, & Rispa, 2003).</p>	<ul style="list-style-type: none"> -erected 	<p>17 Columnas fueron erigidas en ciudad abierta.</p>	<p>Se levantaron 17 columnas diferentes en la misma superficie.</p>	<ul style="list-style-type: none"> -level -prove 		

Building the column starts drawing the geotextile, then fixing it to the rigid parts, the formwork is attached to the foundation and then the concrete is poured inside. The whole building process took place in a normal build place with the students, no qualified workers where required.

-building
-normal

No hacen faltas
especializados para la
construcción

Reinforced concrete up to date had only the possibility to be done in prismatic figures done with rectilinear surfaces. The flexible formwork permits double curvature surfaces giving place to a new organic form for this architectonic element (Figure 6).

-concrete
-new organic
form

Encofrados flexibles
permiten figuras con doble
curvatura a diferencia de
los encofrados rígidos.